

# Basic Gravel Stop



## Product Features

- Continuous cleat of gravel stop is fastened into the face along the wall
- Gravel stop cap is locked onto the cleat and then fastened into the roof
- Roof flange of gravel stop is stripped in with appropriate roofing material
- Gravel stop and cleat are formed in 10 ft. sections and joined to allow for longitudinal expansion and contraction
- Individual gravel stop sections are joined with 6 in. back-up plates
- Installation of this gravel stop is very straightforward and the design allows for easy in field customization and adjustments
- This type of gravel stop is more resistant to oil canning caused by uneven (wavy, bulky...) wood blocking
- Wide variety of colors and material thicknesses is available with short lead times

## Materials

- 27 Kynar 500 colors from Englert Color Chart are stocked in 0.032", 0.040", 0.050" Aluminum, 22 & 24 GA Steel
- Mill finish products can be fabricated in various metal thicknesses
- Stainless Steel, Copper and Zink are available with short lead times
- BM Fixed Anchor Coping can also be fabricated from flat stock purchased off any available sheet metal manufacturer on the market (Drexel Metals, ATAS, PAC-CLAD, Firestone, etc.)

## Warranty

- 35 year color warranty when fabricated from Englert flat stock
- Lifetime Total System warranty is available on commercial projects

Bensalem Metal Inc.  
2424 State Rd., Section 3  
T: (215)52603355 F: (267)430-7740  
Website: [www.bensalemmetal.com](http://www.bensalemmetal.com) Email: [contact@bensalemmetal.com](mailto:contact@bensalemmetal.com)

